

4FT/5FT REPLACEMENT LED LUMINAIRE

- Uses 0.06W SMD LED.
- Isolating TUV/ETL/UL approved driver.
- Universal input voltage from AC90-277V.
- Safety operating voltage from DC36-DC40V.
- IP65 protection level.
- Support for pendant, ceiling, wall mounting.
- Extremely low maintenance.
- Durable structure and stable performance.
- No blink during operating
- CE/Rohs approval



1.5M-50W

Item Code:	OS-P65S5-50-X		Description	IP65 Tri-Proof LED Light	
Dimension	mm	1570*134*94	Viewing Angle	Degree	120
LED Type	Taiwan chip	SMD3528	Colour Index	Ra	70-75
LED Qty	pcs	732	Power Factor	PF	>0.95
Housing Material	PC housing+PC cover+AL board		LED forwarder Current	mA	18-19mA
Luminous (LM)	4000-4200 LM		Luminous Flux (5000-5500k)	1M	1100-1150
				2M	380-390
				3M	205-210
Luminous Efficiency	LM/W	80-85	Environment Temperature	°C	-20 – +40
Input Voltage	V	AC90-265	Waterproof	Level	IP65
Work Voltage	V	DC36-42	Lifespan	Hr	30000
Power Consumption	W	50W	Warrenty	Year	3
Colour Temperature	TC	WW: 3000-3500K, 3500-4000K, 4000-4500K, PW: 4500-5000, 5000-5500, 5500-6000K, CW: >6000K			
Packing	Carton Size: 1595*450*340mm, 6pcs/carton				

1.2M-50W

Item Code:	OS-P65S4-50-X		Description	IP65 Tri-Proof LED Light	
Dimension	mm	1270*134*94	Viewing Angle	Degree	120
LED Type	Taiwan chip	SMD3528	Colour Index	Ra	70-75
LED Qty	pcs	732	Power Factor	PF	>0.95
Housing Material	PC housing+PC cover+AL board		LED forwarder Current	mA	18-19mA
Luminous (LM)	4000-4200 LM		Luminous Flux (5000-5500k)	1M	1100-1150
				2M	380-390
				3M	205-210
Luminous Efficiency	LM/W	80-85	Environment Temperature	°C	-20 – +40
Input Voltage	V	AC90-265	Waterproof	Level	IP65
Work Voltage	V	DC36-42	Lifespan	Hr	30000
Power Consumption	W	50W	Warrenty	Year	3
Colour Temperature	TC	WW: 3000-3500K, 3500-4000K, 4000-4500K, PW: 4500-5000, 5000-5500, 5500-6000K, CW: >6000K			
Packing	Carton Size: 1295*450*340mm, 6pcs/carton				

Lamp Specialists Wgtn Ltd
PO Box 31199
Lower Hutt

Phone 04 5685815 Fax 04 5683741

EMAIL :: sales@lampspecialists.co.nz