




Photocrescenta lamps have an internal white coating, which emits diffused, very uniform light at high luminous output. Max. permissible base temperature is 250° C. The burning position of Photocrescenta lamps is universal.


Application

- Black-and-white photographic enlargers




Dimensions in mm

Type	A nom.	B max.
Cap/base E27		
PF603E	60.0	107.5
PF605E/PF607E	65.0	123.5



PF605B B22d



Burning position

Type	W	V	Cap/ base	Finish	ANSI code	LIF code	Lumen output lm	Correlated colour temperature K	Lamp life 50% h	Ordering number
75W										
PF603E/51	75W	230V	E27	INTERNAL WHITE	-	P3/3	1100	2800	100	9205 311 44200
PF603E/51	75W	240V	E27	INTERNAL WHITE	-	P3/3	1100	2800	100	9205 311 45500
150W										
PF605B/51	150W	240V	B22D	INTERNAL WHITE	-	P3/4	2500	2800	100	9205 320 45500
PF605E/51	150W	230V	E27	INTERNAL WHITE	-	P3/4	2500	2800	100	9205 321 44200
PF605E/51	150W	240V	E27	INTERNAL WHITE	-	P3/4	2500	2800	100	9205 321 45500
250W										
PF607E/51	250W	230V	E27	INTERNAL WHITE	-	P3/6	6500	3000	3	9205 326 44200
PF607E/51	250W	240V	E27	INTERNAL WHITE	-	P3/6	6500	3000	3	9205 326 45500