



PF207E E27

Photolita lamps have an internal white coating, which emits diffused uniform light. The colour temperature matches the sensitivity of monochrome and colour films. The PF217E has an internal mirror and can be used without a separate reflector. The burning position of Photolita lamps is universal.

Applications




- General photographic and cine lighting
- On-stage table lamps and other domestic-type luminaires




PF208E E27



PF217E E27 Dimensions in mm




Luminous intensity in centre of beam cd	Angle at half luminous intensity in centre of beam
3300	2 x 35°



PF217E E27

Type	A nom.	B max.
Cap/base E27		
PF207E	60.0	107.5
PF208E	80.0	169.5

Type	A nom.	B max.
Cap/base B22d		
PF207B	60.0	106.0
PF208B	80.0	162.5



Burning position

Type	W	V	Cap/base	Finish	ANSI code	LIF code	Lumen output lm	Correlated colour temperature K	Lamp life 50% h	Ordering number
250W										
PF207E/21	250W	220V	E27	INS FROSTED ²⁾	-	P1/1	7500	3400	3	9205 253 42900
PF207E/21	250W	230V	E27	INS FROSTED ²⁾	-	P1/1	7500	3400	3	9205 253 44200
PF207E/21	250W	250V	E27	INS FROSTED ²⁾	-	P1/1	7500	3400	3	9205 253 46200
PF217E/44	250W	220V	E27	REFL SAT FROST ¹⁾	-	P1/6	NA	3400	3	9232 155 42900
PF217E/44	250W	240V	E27	REFL SAT FROST ¹⁾	-	P1/6	NA	3400	3	9232 155 45500
275W										
PF207B/21	275W	240-250V	B22D	INS FROSTED ²⁾	-	P1/1	7500	3400	4	9205 275 45700
PF207E/21	275W	240-250V	E27	INS FROSTED ²⁾	-	P1/1	7500	3400	4	9205 277 45700
500W										
PF208B/21	500W	240V	B22D	INS FROSTED ²⁾	-	P1/2	14800	3400	6	9205 262 45500
PF208E/21	500W	220V	E27	INS FROSTED ²⁾	-	P1/2	14800	3400	6	9205 265 42900
PF208E/21	500W	240V	E27	INS FROSTED ²⁾	-	P1/2	14800	3400	6	9205 265 45500

¹⁾ Reflector, satinated and frosted

²⁾ Inside frosted

